

NITRILE	GREEN & BLUE	FLOCK-LINED	S-XXL	DIAMOND GRIP	CHEMICAL RESISTANT
---------	--------------	-------------	-------	--------------	--------------------

Chemical and solvent resistant green glove with flocklined interior for comfort. Specially formulated premium grade acrylonitrile butadiene rubber for combination of improved protection and dexterity. Can be worn with minimal finger fatigue. Raised diamond pattern for sustained grip and special thickness for protection from abrasion, tears, cuts and punctures. Recommended for use in for example industrial chemical processing, automotive paints, battery manufacturing, horticulture, pesticide handling, agriculture, laboratory testing, environmental waste cleanup, air compressor manufacturing, degreasing, leather tanning, glue manufacturing.

### Characteristics

<b>Suitable for latex allergic people.</b>	<b>Grip improving texture on palms and fingers</b>
<b>Special formula nitrile butadiene rubber</b>	<b>High resistance against solvents, fats</b>
<b>Flock-lined for absorption of perspiration</b>	<b>Protection from bacteria and virus</b>
<b>Ergonomic, minimal finger fatigue</b>	<b>Strong protection from abrasion</b>

### Packaging

- 144 pairs per carton (12x 12 pairs)
- Each pair individually packed
- Dimension of pack: 450 x 150 x 10mm



**Labelling** Manufacturing date, expiration date, batch number, reference and EAN code. Product name in multiple languages e.g.: Spanish, English, French, German, Italian, Portuguese.

CE marking, protection pictograms, safety standards and legislation. Size, size guide and units.

## Standards:

- CE marking PPE Category III according to Regulation (EU) 2016/425
- EN ISO 374-1:2016 (Type A)
- EN ISO 374-5:2016 Protection against micro-organisms
- EN 420:2003+A1:2009
- EN 388:2006. Protection against mechanical risks (abrasion, blade cuts, tears, punctures, sharp cuts)

## Chemical resistance:

### PERMEATION (EN ISO 374-1:2016/A1.2018, type A)

Gloves are classified in terms of time of passage, according to each individual chemical for which the glove resists permeation:

CHEMICALS	LEVEL	LETTER
METHANOL	4	A
N-HEPTANE	6	J
SODIUM HYDROXIDE 40%	6	K
SULPHURIC ACID 96%	4	L
ACETIC ACID 99%	4	N
AMMONIA 25%	6	O
HYDROGEN PEROXIDE 30%	6	P
FORMALDEHYDE 37%	6	T

## Performance Level:

Time (min)	> 10	> 30	> 60	> 120	> 240	> 480
Performance Level	1	2	3	4	5	6

## DEGRADATION

Degradation % (DR) is determined for each chemical used in the permeation tests.

- (DR) J: N-HEPTANE 5.1%
- (DR) K: SODIUM HYDROXIDE 40% -13.3%
- (DR) L: SULPHURIC ACID 96% 61.8%
- (DR) O: AMMONIA 25% -5.9%
- (DR) P: HYDROGEN PEROXIDE 30% -5.2%
- (DR) T: FORMALDEHYDE 37% -3.0%

The “SUPER NITRILE® RNF15” glove PPE should be used to protect the user’s hand against chemical risks (products and levels mentioned above) and against microbiological risks.

The present PPE should never be used against other risks than those described above. The use of his PPE should be evaluated correctly depending on the place of work.



GLOVE SIZES		S	M	L	XL	XXL
Length	mm	330	330	330	330	330
Palm thickness	±0,02 mm	0.40	0.40	0.40	0.40	0.40



Pair



Polybag packing per pair



Pack per 12 pairs